

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-24 have been cancelled, without prejudice.

25. (New) An anoscope, comprising a first hollow body open at opposite ends and a second hollow body open at opposite ends shapingly coupled with said first hollow body and arranged to coaxially rotate inside said first hollow body, said second hollow body being provided with a window arranged to make a portion of rectal mucous membrane accessible, wherein said window has dimensions and a shape such as to enable a surgical device to intervene on said portion.
26. (New) An anoscope according to claim 25, and furthermore comprising an angular positioning element arranged to adjust the relative angular position of said second hollow body in said first hollow body in preset reciprocal angular positions.
27. (New) An anoscope comprising a first hollow body open at opposite ends and a second hollow body open at opposite ends shapingly coupled with said first hollow body and arranged to coaxially rotate inside said first hollow body, said

second hollow body being provided with a window arranged to make a portion of rectal mucous membrane accessible, wherein an angular positioning element is furthermore provided arranged to adjust the relative angular position of said second hollow body in said first hollow body in preset reciprocal angular positions.

28. (New) An anoscope according to claim 27, wherein said window has dimensions and a shape such as to enable a surgical device to intervene on said portion.
29. (New) An anoscope according to claim 25, wherein said first hollow body comprises a first truncated-cone portion.
30. (New) An anoscope according to claim 29, wherein said first truncated-cone portion is solidly connected with a second truncated-cone portion that has a progressively decreasing cross-section.
31. (New) An anoscope according to claim 30, wherein said second truncated-cone portion is solidly connected with a third truncated-cone portion that protrudes from a part opposite said first truncated-cone portion and has a progressively decreasing cross-section.

32.(New) An anoscope according to claim 27, wherein said first hollow body has an edge positioned in such a way that it faces the operator during use.

33. (New) An anoscope according to claim 32, wherein said second hollow body comprises a rotation segment and an operating segment, that can be associated with one another before use.

34.(New) An anoscope according to claim 25, wherein said second hollow body comprises a rotation segment and an operating segment, that can be associated with one another before use.

35.(New) An anoscope according to claim 34, wherein said window is arranged on said operating segment.

36.(New) An anoscope according to claim 25, wherein said window comprises an operating window.

37.(New) An anoscope according to claim 36, wherein said operating window is defined by a U-shaped cut.

38.(New) An anoscope according to claim 25, wherein said window opens near to the point that can be reached by the tip of an index finger of an hand of an

individual of medium build, by inserting said index finger inside said second hollow body.

39.(New) An anoscope according to claim 33, wherein said edge comprises a plurality of notches.

40.(New) An anoscope according to claim 39, wherein said notches are 6 in number.

41.(New) An anoscope according to claim 40, wherein said notches are arranged along said edge according to the hours on an imaginary clock-face.

42.(New) An anoscope according to claim 41, wherein said notches are arranged at 1 o'clock, 3 o'clock, 5 o'clock, 7 o'clock, 9 o'clock, 11 o'clock.

43.(New) An anoscope according to claim 39, wherein said angular positioning element is integral with said rotation segment.

44.(New) An anoscope according to claim 43, wherein said angular positioning element comprises a plurality of teeth.

45.(New) An anoscope according to claim 44, wherein said plurality of teeth comprises a locking tooth.

46.(New) An anoscope according to claim 45, wherein said locking tooth comprises a recess housing a peg.

47.(New) An anoscope according to claim 46, comprising an elastic element interposed between said peg and the bottom of said recess.

48.(New) An anoscope according to claim 46, wherein the rotation of said angular positioning element can be locked by an interaction between said peg and each of said notches.